






BUILT BY OPERATORS FOR OPERATORS.

The MUSKOX 23-78 clears snow fast. The blower's unique design allows you to be gentle on soft surfaces like stamped concrete, gravel, and grass while giving you the ability to get aggressive with ice at any time. And our innovative backdrag capability clears snow in front of doors and next to buildings. So you don't waste time shoveling.



and energy and reduce your risk of damaging grounds or properties all while staying safe in the cab.

Call to learn more:





An innovative blower to clear snow and ice fast.



MUSKOX 23-78

The MUSKOX23-78 redefined the game in the snow removal industry. The bi-directional blower's revolutionary features reduce time on sité. And its versatility replaces several single task machines.

FEATURES

BACKDRAG AND BLOW

The patented back dragging ability is where the MUSKOX truly shines. It cleans snow right up against buildings, doors, fire hydrants or other obstructions, saving you time and greatly reducing the need to shovel.

TOP RUBBER CUT EDGE

And while back dragging, the Top Rubber Cut Edge acts like a squeegee to gently clear snow and moisture, reducing ice buildup and the need to salt.





LEVELING WHEEL NEW

Our brand new Leveling Wheel helps you line up the MUSKOX perfectly every time, finding the optimal angle to Blow, Shear Ice, or Backdrag. This decreases training time for operators, getting you up and running faster and safer.







SIX BLADED BLOWER FAN NEW

Our new and improved six bladed fan blows snow more efficiently, allowing you to clear snow faster.

GLIDE PLATE

The design of the glide plate allows the blower to skim over the surface, protecting softer substrates and lawns.

OPTIONAL DUAL AUGER

The optional Dual Auger chews through big snow faster and speeds up back dragging operations.



LOWERED CHUTE

The lower height of the chute gives you excellent visibility and reduces the risk of plugging.

BOTTOM CUT EDGE

Tilt the MUSKOX into the Shear position and engage the Lower Cut Edge to instantly get more aggressive with ice and compacted snow.

Specifications

Opcomoduona			
MODEL	23-78 SINGLE		23-78 DUALLY
FLOW			
Туре	Low, Standard, High		
Rate	14-50 gpm		
CUTTING EDGE			
Туре	Low, Standard, High		
Width		78"	
BLOWER FAN			
Diameter		21"	
SERRATED AUGER			
Top Auger	N/A		10" Diameter
Bottom Auger	18" Diameter	1	18" Diameter
MOTORS			
Trice	Auger, Fan, Chute		
APPROXIMATE WEIGH	IT		
Landed	1107 lbs]	1167 lbs
CHUTE & DEFLECTOR CONTROLS			
Electric over hydraulic			
DIMENSIONS			
79 L x 53 W x 58 H			