

22-78

DUALLY BI-DIRECTIONAL
SNOWBLOWER



22-78

SNOWBLOWER

DUALLY OPTIONAL



SPECIFICATIONS

FLOW	
Type	Low, Standard, High
Rate	14-45 gpm
CUTTING EDGE	
Type	Steel, Rubber
Width	78"
BLOWER FAN	
Diameter	21"
SERRATED AUGER	
Diameter	18"
MOTORS	
Trice	Auger, Fan, Chute
APPROXIMATE WEIGHT	
Landed	1097 lbs
CHUTE & DEFLECTOR CONTROLS	
Electric over hydraulic	
DIMENSIONS	
79L x 53W x 58H	

DUALLY SPECIFICATIONS

SERRATED AUGER DIAMETER	
Upper	10"
Lower	18"
APPROXIMATE WEIGHT	
Landed	1157 lbs

FEATURES

BACK DRAGGING

Our patented back drag feature allows operators to blow snow while back dragging in front of obstructions such as garage doors, siding, and fire hydrants. This saves time and money, while lowering injury risk by decreasing manual labor.

GLIDE PLATE AND LOWER CUTTING EDGE

The glide plate allows you to glide over grass and gravel without ripping up the soft surfaces. Subsequently, create an instant torque on the lower cutting edge to break up snow and ice to better expose hard surfaces.

LOWERED CHUTE

Our lowered chute improves operator visibility and decreases snow dust while blowing snow. There is a standard UHMW plastic inside the chute that increases efficiency, while decreasing chute plugging.

DUAL AUGER

Our optional dual auger, called the dually, helps the operator eat through big snow falls, ice crusted snow, and blow more snow while back dragging.



MUSKOXMN.COM